



benton international

BAKERY RANGE

ROTARY OVEN

Can choose Electric & Gas
trolley Size 18 & 36 Tray

Baking a wide Range:

Bread, Toast, Cookies, Cakes, Etc.

- Efficient low-energy, super insulation.
- Overheating protection, safe and reliable.
- One operator can save manpower.
- Full Stainless Steel body.
- Computer control panel, simple to operate.
- Steam humidification function.
- Special Designed system to ensure uniform.
- Hot-air and temperature inside the oven.

Inside : 1.5mm thickness stainless steel;
Outside : 1.2mm thickness stainless steel
Schneider electronic accessories;
High Quality heating tube 135mm thickness.



ELECTRIC/GAS ROTARY OVEN

MODEL	BT-RO-18 (E)	BT-RO-36 (E)	BT-RO-18 (G)	BT-RO-36 (G)
Voltage	380/3/50Hz or 380/3/60Hz	380/3/50Hz or 380/3/60Hz	380/3/50Hz or 380/3/60Hz	380/3/50Hz or 380/3/60Hz
Power	30.0kw	46.0kw	1.5kw	2.5kw
Gas	NA	NA	LPG/PNG	LPG/PNG
Temperature	RT 350 °C	RT 350 °C	RT 350 °C	RT 350 °C
Trolley	1	2	1	2
Tray	18	36	18	36
Net Weight (kg)	1600	3200	1600	2200
Dimension (L x D x H)	1800 x 1700 x 2400	2200 x 2000 x 2400	1800 x 1700 x 2400	2200 x 2000 x 2400

BAKERY RANGE

DOUGH SHEETER



TECHNICAL DATA

MODEL	BT-DS-520B	BT-DS-520	BT-DS-650
Dimensions (LxWxH) mm	2080x880x620	2550x380x1180	2950x1100x1180
Working Position	2080/620	2550/1180	2950/1180
Maximum Roll Weight	5-7	5-7	6-8
Power (kw)	0.56	0.56	0.75
Conveyor Belt Size	2000x500	2000x500	2400x600
Voltage	220v-380v-50HZ-1/3HP		
Roller Adjust Gap	1~35mm	1~35mm	1~35mm

BREAD SLICER



TECHNICAL DATA

MODEL	BT-BS-31	BT-BS-39
Dimension (LxWxH)mm	630x630x685	675x630x740
Blade Frame Width (mm)	385	485
Output (pcs.)	240/per hr	240/per hr
Power (kw)	0.2	0.2
Thickness of Slice (mm)	12	12
Voltage (v)	220v~400v-50/60Hz-3HP	

PLANTARY OR PLANETARY MIXER WITH SAFETY GUARD



TECHNICAL DATA


MODEL BT-PM-Deluxe	200G	300G	400G
Dimensions (LxWxH) mm	460x440x810	580x500x995	580x500x1000
Capacity	20 Qt	30 Qt	40 Qt
Power (kw)	0.56	0.75	1.5
Rev/Min	92 / 176 / 337	87 / 174 / 337	87 / 174 / 337
Voltage (v)	220v~400v-50/60Hz-3HP		

TECHNICAL DATA

MODEL	BT-SM-50	BT-SM-75	BT-SM-90
Dimensions (LxWxH) mm	850x490x1070	940x540x1260	1000x540x1300
Dough Capacity (kg)	20	40	60
Floor Capacity (kg)	12.5	25	38
Bowl Capacity (Qt)	50	75	90
Power (kw)	2.25	2.25	3.75
Voltage (v)	220v~400v-50/60Hz-3HP		



S/S Whisk



S/S Bat



S/S Hook



SPIRAL MIXER





benton international

BAKERY RANGE

DOUGH DIVIDER



TECHNICAL DATA

MODEL	BT-MM-280
Dimensions (LxWxH) mm	1000 x 530 x 1060
Roller Working Width	280
Roller Size (mm)	95 x 280 (w)
Maximum Roll Weight	30-350g
Voltage/Power (v/kw)	220v~400v-50/60Hz-3HP

DOUGH DIVIDER / ROUNDER MACHINE



TECHNICAL DATA

MODEL	BT-DD-30	BT-DD-30A
Dimensions (LxWxH)mm	850 x 750 x 1500	850 x 750 x 1500
Dough Weight (g)	30-100	25-85
Power (kw)	0.75	0.75
Capacity / time	30pcs. / time	36pcs. / time
Net Weight (kg)	360	360

ELECTRIC OVEN SPECIFICATION

- Upturned glass door with Separate handles for hand protection.
- Separated controlling panel. easy for operation and time control.
- Visible glass widow to permit Real-time control of baking conditions.
- Efficient heating tube makes baking more balanced.

- Inner liner is made of plating aluminium plate, which is more durable and though under high temperature.
- Smoke - absorbing design for the hood to keep the whole machine more clean.
- Thicken insulation design to keep the heat inside.



TECHNICAL DATA

Model No.	MGE-2Y-4
Temperature Range	0~400 °C
Rated Voltage	380V
Rated Frequency	50Hz
Rated Power Input	9.96kW
Net Weight (kg)	355
Exterior Dimension (mm)	1260x1360x1780



BAKERY RANGE



BAKING OVEN / ELECTRIC DECK OVEN / INFRARED DECK OVEN / GAS DECK OVEN

TECHNICAL DATA

Model	Voltage (V)	Power (Kw)	Capacity	Dimensions (mm)	Chamber Size (mm)	Weight (kg)	Electric/Gas
BT-YXD-10C	220	3.2	1 Deck / 1 Tray	925x570x430	640x455x180	68	Electric
BT-YXD-20C	220/380	6.6	1 Deck / 2 Tray	1260x805x535	860x670x220	75	Electric
BT-YXD-40C	380	13.2	2 Deck / 4 Tray	1260x805x1100	860x670x220x2	135	Electric
BT-YXD-60C	380	19.8	3 Deck / 6 Tray	1260x805x1515	860x670x220x3	206	Electric
BT-YXD-13C	380	9	1 Deck / 3 Tray	1770x840x615	1300x670x220x3	105	Electric
BT-YXD-26C	380	18	2 Deck / 6 Tray	1700x805x1100	1300x670x220x6	190	Electric
BT-YXD-90C	380	25.2	3 Deck / 9 Tray	1700x805x1515	1300x670x220x9	290	Electric
BT-XYX-20A	220	0.1	1 Deck / 2 Tray	1330x840x615	860x670x220x2	99.5	LPG
BT-XYX-40A	220	0.2	2 Deck / 4 Tray	1330x840x1190	860x670x220x2	185	LPG
BT-XYX-60A	220	0.3	3 Deck / 6 Tray	1330x840x1660	860x670x220x3	256	LPG
BT-XYX-13A	220	0.1	1 Deck / 3 Tray	1770x840x615	1300x670x220x3	150	LPG
BT-XYX-26A	220	0.2	2 Deck / 6 Tray	1770x840x1190	1300x670x220x6	256	LPG
BT-XYX-90A	220	0.3	3 Deck / 9 Tray	1770x840x1660	1300x670x220x9	328	LPG
BT-NFD-40FF	380	1.2+3.5	0:4 Tray / P:8 Tray	1460x1190x1980	-----	538	Electric